

Conventional folding machine



multimaster 38/4/4-FSA

>> Unsurpassed Fold Quality in Two Basic Versions

multimaster 38-40

The roller diameter of 40 mm makes the multimaster 38-40 the ideal allround folder which can be used for all common folding jobs.

multimaster 38-30

Fold rollers with a diameter of 30 mm make the multimaster 38-30 especially suitable for handling small folds and light stock.

multimaster 38

multimaster 38-40



Combination fold plate UFT with integrated deflector. Setting of fold plate stop and engagement of deflector by hand wheel.

Standard Equipment

Number of fold units: 1 or 2
Number of fold plates: 4
Fold roller diameter: 40 mm
Fold rollers: Polyurethane/steel or Perbunan
Top-loading bottom-feed air feeder PBA or
Flat pile feeder FSA
Shingle delivery
Fold units of folder lines 38-40 and 38-30 are compatible

Specifications:

Paper sizes:
max. 38 x 65 cm; min. 7 x 12 cm
Fold length:
max. 46,5 cm; min. 3,5 cm / 1,8 cm
Paper weight:
40 to 250 g/m²
Speed:
max. 200 m/min. (depending on material)

multimaster 38-30



Standard fold plate SFT in conventional design.

Standard Equipment

Number of fold units: 1 or 2
Number of fold plates: 4 or 6
Fold roller diameter: 30 mm
Fold rollers: Polyurethane/steel or Perbunan
Top-loading bottom-feed air feeder PBA or
Flat pile feeder FSA
Shingle delivery
Fold units of folder lines 38-30 and 38-40 are compatible

Specifications:


Paper sizes:
max. 38 x 65 cm; min. 7 x 12 cm
Fold length:
max. 35,0 cm; min. 3,0 cm / 1,8 cm
Paper weight:
40 to 200 g/m²
Speed:
max. 200 m/min. (depending on material)




multimaster 38



>> Increased benefit through optional equipment




MS 45
Mobile knife fold unit
 Usable after 1st or 2nd fold unit
 Knife rotates by 180°
 Infeed width: max: 450 mm; min. 120 mm
 Infeed length: max. 330 mm; min. 100 mm



Combination fold plate UFT
 for multimaster 38-40




KF 31
Attachable additional fold unit
 with two fold plates
 Especially for small folds
 Infeed width: max: 310 mm
 Fold length: max. 110 mm; min. 18 mm



Fold plate for small formats
 KFT to produce small folds
 down to 18 mm
 for multimaster 38-30



Gluing device



SKM 36
Small format vertical stacker
 Prevents small folds from opening up
 Infeed width: max: 360 mm; min. 50 mm




Plough fold




Reading device

Gate fold plate
 Ionization bars
 Kicker for delivery
 Cutting, scoring and perforation tools

>> Other machine versions



multimaster 38/4-PBA



multimaster 38/4/4-PBA

